Liangsu Masterbatch Technology Co Ltd

No.8,2nd Street,huaxia 2nd huan Road,Huaxia Industrial Zone,Qiaotou Town,Dongguan,China

Zhihe Masterbatch Technology Co Ltd

No.17,Yinhu 2nd Road,Shishuikou Village,Qiaotou Town,Dongguan,China Post code: 523520

Web: www.lsm-china.com Email: qi-andy@foxmail.com Mob: +86-15902018396 Tel: +0086-769-82521311 Fax: +0086-769-82521318

# ZHIHE INTERNA TIONAL TRADING CO., LTD





ZHIHE MASTERBATCH TECHNOLOGY CO LTD





# COMPANY PROFILE

Zhihe International Trading Co. Ltd, located in ShenZhen City, Guangdong province, China, is a large professional international trading company mainly work on searching, producing and exporting masterbatch, own directly mast e rbatch manufacturer: Zhihe Mas terbatch Technology Co. Ltd, Lia ngsu Masterbatch Technology Co . Ltd.







We have 10 advanced production lines, include twin-screw extrud er, single screw extruder, internal mixer, High mixing machine, Plastic grinder machine, Three axis grinding machine and ot her complete testing equipment( colorimeter, density instrumen t, muffle furnace, film blowing machine, extruding machine, moistu re meter, Liquidity meter...), yearly output value can reach 50 mill ion dollars, years 21 years experience in color blending, complet e development system, will let you feel satisfied with our products.

Selling products include black masterbatch, white masterbatch, color masterbatch, functional masterbatch( filler masterbatch, desiccant masterbatch, toughening masterbatch, whitening masterbatch, anti-foaming masterbatch, slip masterbatch, antistatic masterbatch, transparent masterbatch, flame retardant masterbatch, anti-UV masterbatch and so on), granulation, modified plastic and engineering plastics.

We have passed the ISO9001-2000 quality management system and all of our products reach ROHS quality standard. Widely used in blow film, injection molding, extrusion, flow delay, non-woven fabric, blow molding, pipe, plate, sheet, pearl cotton and other fields.

With us your money in safe, your business in safe. Cooperate with us, you don't need to worry about quality, service, delivery time, payment term and documents, we will cover all the bases for you. Warmly welcome come for a visit





# CONTENTS

- **P4** — Complete Testing Equipment
- **P5** — High Concentration Black Masterbatch
- **P6** — High Concentration White Masterbatch
- **P7** — High Concentration Color Masterbatch
- **P8** — Filler Masterbatch
- **P9** — Functional Masterbatch
- **P10** — Granulation







# **COMPLETE TESTING EQUIPMENT**


Our factory have strong technical force, advanced production technology, full range of testing equipment to make a high-quality protection.





**Liquidity Tester** 









### **HIGH CONCENTRATION BLACK MASTERBATCH**



#### Application & Features

This series products is in good dispersion, low cost of coloration, the content of carbon black can reach 55%, widely used in blow film, injection molding, extrusion, blow molding, pipe, pearl cotton and other fields, suitable for PE PP ABS PET EVA AS PS PC PVC ... if you have any special requirement, we can still cus tomize for you.

#### Main Technical Index

NO.	ltem	Technical Index
1	Outer appearance	Column Grain
2	Heat-resistance	150-300°C
3	Light fastness	Level 5-8
4	Carbon black content	10%-55%
5	Liquid water	<0.15

#### **Recommend mixture proportion**

1%-4%; Clients may also adjust the mixture according to their special requirements.

#### Use method

Mix masterbatch with plastic resin in right proportion.











# **HIGH CONCENTRATION WHITE MASTERBATCH**







#### Application & Features

This series products have features include high concentration, good dispersion, low cost of coloration, the content of titanium dioxide can reach 70%, widely used in blow film, injection molding, extrusion, blow molding, pipe, pearl cotton and other fields, also suitable for PE PP ABSPET EVA AS PC PS PVC... if you have special requirement, we can still customize for you.

#### **Recommend mixture proportion**

1%-4%; Clients may also adjust the mixture according to their special requirements.

#### Use method

Mix masterbatch with plastic resin in right proportion.

#### Main Technical Index

NO.	Item	Technical Index
1	Outer appearance	Column Grain
2	Heat-resistance	150-300°C
3	Light fastness	Level 5-8
4	Titanium dioxide content	15%-70%
5	Liquid water	<0.15









## **HIGH CONCENTRATION COLOR MASTERBATCH**

#### Application & Features

This series products have features include high density, good dispersion, low cost of coloration, the content of pigment can reach 50%, widely used in blow film, injection molding, extrusion, blow molding, pipe, pearl cotton and other fields, also suitable for PE PP ABS PA PC PS PVC..... if you have special requirement, we can still customize for you.

#### Recommend mixture proportion

1%-4%; Clients may also adjust the mixture according to their special requirements.

#### Use method

Mix masterbatch with plastic resin in right proportion.

#### 📕 Main Technical Index

NO.	Item	Technical Index
1	Outer appearance	Column Grain
2	Heat-resistance	150-300°C
3	Light fastness	Level 5-8
4	Dispersion performance	Without color spot, colour flow
5	Migration	≥Level 4
6	Liquid water	<0.15





App This resi Fille can

> **Rec** 5%. spe

Use Mix









# **FILLER MASTERBATCH**

#### Application & Features

This series products can change physical property of plastic resin to reach client' requirements, also it can reduce the cost. Filler masterbatch include Caco3 filler, Baso4 filler, Talc filler, all can customize base your requirements.

#### Main Technical Index

NO.	Item	Technical Index
1	Outer appearance	Column Grain
2	Heat-resistance	150-300°C
3	Light fastness	Level 5-8
4	CACO3 content	70%-85%
5	Liquid water	<0.15

#### Recommend mixture proportion

5%-50%; Clients may also adjust the mixture according to their special requirements.

#### Use method

Mix masterbatch with plastic resin in right proportion.











# **FUNCTIONAL MASTERBATCH**

#### Application & Features


Functional masterbatch include whitening masterbatch, antifoaming(desiccant) masterbatch, anti-block masterbatch, slip masterbatch, anti-static masterbatch, transparent masterbatch, flame retardant masterbatch, anti-UV masterbatch and so on, it can change physical property of plastic resin to reach client' requirements.

#### Recommend mixture proportion

0.5%-4%; Clients may also adjust the mixture according to their special requirements.

#### Use method

Mix with plastic resin in right proportion.





**Technical Index** 

Column Grain

150-300°C

Level 5-8

Without color spot, colour flow

≥Level 4 <0.15

Main Technical Index

ltem

Outer appearance

Heat-resistance

Light fastness

Dispersion performance

Migration

Liquid water

NO.

1

2

4

3







### GRANULATION



#### Application & Features

This series products is very convenient to use, clients can use it directly without premix, is a good way to increase production capacity. Can customize by clients' requirements.

#### Main Technical Index

NO.	Item	Technical Index
1	Outer appearance	Column Grain
2	Heat-resistance	150-300℃
3	Light fastness	Level 5-8
4	Migration	≥Level 4
5	Liquid water	<0.2



#### **Recommended mixture proportion**

Use as same as plastic resin, don't need to mix with masterbatch

